

Progress on Designing On-board GRB Trigger

David Wren, Jerry Bonnell, Jay Norris



Recap from DC1...

- We used the raw ~ 15 Hz data, decimated only by removal of events with $\{\phi, \theta\} = \{0, 0\} \rightarrow 12$ Hz. This expedient gave us a quasi-realistic background rate against which to search for GRBs.
- ➤ We used only one N-event sliding window as the first bootstrap step in searching for significant temporal-spatial clustering. Compute Log {Joint (spatial*temporal) likelihood} for tightest cluster in window:

```
Log(P) = \sum Log\{ [1 - cos(d_i)] / 2 \} + \sum Log\{ 1 - (1 + X_i) exp(-X_i) \}
```

> Log(P) threshold set and used to search for GRB trigger



Day 1 Triggers, Panels Top→Bottom:

Log Prob $[\Delta \rho's]$ + Log Prob $[\Delta t's]$

Log Prob [$\Delta \rho$'s]

Log Prob [∆t's]


Raw Rate (includes non-recon'ed γ 's — but we don't use them!)

Similar approach to previous studies:

- (1) Operate sliding 20-event window;
- (2) Find tightest spatial cluster;
- (3) Compute log probs for $\Delta t's$, $\Delta \rho's$ in the selected cluster;
- (4) Exceed threshold value, set to allow < 1 false trigger/6 days?


Real Question is: How many "life-like"

GRBs would be detected?





GRB Trigger regions, 2





Nature of On-board GRB Trigger "Task"

- ► The problem is two-fold:
 - The on-board event trigger rate is expected to be ~ 300 Hz, considerably higher than ~ 30-60 Hz rate for which the unbinned GRB trigger algorithm has been demonstrated to work well ...
 - ... And the event tracks are often not well enough reconstructed, even at high energy where the nearly straight tracks yield the most accurate contributions to the on-board GRB localization.

How to address:

▶ 1st, we need to reduce the event rate that will be considered by a "GRB event buffer" — so that more CPU time is available per event for reconstruction computation.

2nd, we need to make fuller use of the on-board hit information, thereby arrive at better reconstruction for events.



General Approach

- 1. Reduce event rate considered for GRB trigger buffer from ~ 300 Hz to ~ 30-60 Hz: Apply trial subsets of On-board Filters (which are not currently employed), designed to retain as many γ 's as possible (what shall be E dependence?) David Wren has trial filter subsets.
- 2. Per kept event, utilize hit information across towers, reconstructing longer and more accurate tracks, selecting "best" multi-tower track.


Promising approach being explored by Wren is "Hough Transform," which picks out colinear hits in polar coordinate space — looks especially good at higher energies where tracks are straighter (tolerance for track curvature might need to be energy-dependent).

3. Execute GRB trigger algorithm, compute Log {Joint (spatial*temporal) likelihood} for tightest cluster in each sliding temporal window:

$$Log(P) = \sum Log\{ [1 - cos(d_i)] / 2 \} + \sum Log\{ 1 - (1 + X_i) exp(-X_i) \}$$




Which Vetoes Killed Gammas?





Hough Transform


- The basic idea:
 - Transform a coordinate in Cartesian space into a line in (rho, theta) parameter space.
 - Collinear points in Cartesian space have intersecting lines in parameter space
 - Pick out the point of intersection in parameter space, and one gets the line (track) in Cartesian space





22



Hough Transform: Preliminary Results for All Fvents not Vetoed







Hough starts to perform well around 1 GeV, but still has trouble at extreme angles at 100 GeV

David Wren 25



Upwards Moving Albedo at Lower Energies

► Complicating problem: Upwards moving albedo and low-energy cosmic γ 's look very similar, and of course we want to retain the cosmic γ 's for the temporal part of likelihood trigger algorithm.

(Note: Most low-energy γ 's will be retained by the standard filters and sent for ground analysis within the ~ 300 Hz telemetry rate.)

- ► The upwards moving albedo is ~ 140 Hz alone it is considerably higher than our desired rate (30-60 Hz) to-be-presented to trigger algorithm. Must address this additional background component ...
- ▶ David Wren has proposed two fairly successful methods for reducing the upwards moving albedo rate, to ~ 60 Hz, applying the methods only for events in outer towers AND with CalEnergySum = 0:
 - Method 1: require start of "3-in-a-row" to be an {X,Y} pair in the same layer, and be the uppermost hits of a track; OR
 - Method 2: if event comes from direction consistent with cone defined by Earth, then kill it.